

Dekmetal - dodací možnosti platné od 1.1.2015

Profil	DX51D-S320GD Z275 SP25mi					S250GD Z275 SP35mi TEX		S250GD Z275 PU50mi	Al	Al Zn	DX51D-S250GD Z275 FeZn			
	0,5	0,63	0,75	0,88	1	0,5	1	0,5	0,8	0,55	0,5	0,6	0,7	1
TR18/137,5/1100	✓	✓	X	X	X	✓	X	✓	X	✓	✓	✓	X	X
TR 35/207/1035	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
TR 50/263/1040	✓ X	✓	✓	✓	✓	✓ X	✓	✓ X	X	X	✓ X	✓	✓	✓
CR 18/76/1064	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CR40/160/960	X	✓	X	X	X	X	X	X	X	X	X	✓	X	X
<b>RAL</b>														
červená	3000													
vínová	3005													
cihlově-hnědá	3009	3009	3009			3009		3009						
červeno-hnědá	3011													
modrá	5010	5010												
zelená	6005					6020								
šedá	7024	7024			7024	7024	7024	7024						
světle-šedá	7035	7035	7035											
cihlová	8004	8004	8004			8004		8004						
hnědá	8017	8017	8017			8017		8017						
šedobílá	9002	9002	9002		9002									
černá	9005				9005	9004	9004	9005						
stříbrná	9006	9006	9006		9006		9006		9006					
tmavě-stříbrná	9007	9007	9007		9007		9007							
bílá	9010	9010	9010		9010									

TR 50/263/1040 ✓ X Zde může docházet díky velkému profilu a malé tloušťce k vlnění okraje profilu. Tato vlastnost je pouze estetického charakteru. Vyloučeno z reklamace